





<b>MAJOR COMPONENTS</b>	 <b>Android Device</b>	 <b>MTX500 I/O Module</b>
	<b>OPTIONS &amp; ACCESSORIES</b>	<b>Base Options</b> VMT <b>Future Integration Options</b> Job Tracking Battery Monitoring Pallet Detection
<b>USER</b>		<b>TRUCK</b>

## metrix by TotalTrax - Product Specifications and Operating Requirements

Specification Name	MTX500
Operating Temperature	-4°F to +140°F / -20°C to +60°C
Operating Humidity	0-100% non-condensing
Operating Shock	10G (nondestructive) / 100G (destructive)
Case Size	2.25in x 4.50in x 3.5in
Case Material	Aluminum & Plastic
Case Rating	NEMA 4X/IP66
Relay Output	Relay 1 (Horn): NO (normally open), Max 30 VDC, 5A Relay 2 (Drive): NO, Max 30 VDC, 16A - (Continual, normally open)
Output Alarm	N/A
Data Retrieval	N/A
Radio Specifications	N/A
WiFi Ports	N/A
Analog Inputs	A10: 0-80 VDC / AI1, AI -0-12
Digital Inputs	Off - (Three DI) VDC On: > = 5 VDC Max 80 VDC
Base Display	N/A

To learn more, visit [totaltraxinc.com](http://totaltraxinc.com) or call 302.514.0600.  
 Customer Service: 855.895.7720 | Technical Service: 855.895.7721  
 920 West Basin Road, Suite 402 | New Castle, DE | 19720 | USA